



CADENA FABRICADA SEGÚN NORMA ISO 9001
 CHAIN PRODUCED BY ISO 9001 CERTIFIED COMPANY

CADENA ESTIRADA / PRE-STRETCHED CHAINS



SIMPLE

| ISO | p | | b ₁ mm min. | d ₂ mm | d ₁ mm max. | a ₂ mm max. | g mm max. | F _s min KN | q kg/m ≈ |
|--------------|--------|------|------------------------------|----------------------|------------------------------|------------------------------|-----------------|-----------------------------|----------------|
| | mm | inch | | | | | | | |
| 08B-1 | 12,7 | 1/2" | 7,75 | 4,45 | 8,51 | 17,0 | 11,5 | 17,8 | 0,75 |
| 10B-1 | 15,875 | 5/8" | 9,65 | 5,08 | 10,16 | 19,6 | 13,9 | 22,2 | 0,98 |
| 12B-1 | 19,05 | 3/4" | 11,68 | 5,72 | 12,07 | 22,7 | 16,1 | 28,9 | 1,24 |
| 16B-1 | 25,4 | 1" | 17,02 | 8,28 | 15,88 | 36,1 | 21,0 | 60,0 | 3,30 |

DOBLE

| ISO | p | | b ₁ mm min. | d ₂ mm | d ₁ mm max. | a ₂ mm max. | g mm max. | e mm | F _s min KN | q kg/m ≈ |
|--------------|--------|------|------------------------------|----------------------|------------------------------|------------------------------|-----------------|---------|-----------------------------|----------------|
| | mm | inch | | | | | | | | |
| 10B-2 | 15,875 | 5/8" | 9,65 | 5,08 | 10,16 | 36,2 | 13,9 | 16,59 | 44,5 | 1,97 |
| 12B-2 | 19,05 | 3/4" | 11,68 | 5,72 | 12,07 | 42,2 | 16,1 | 19,46 | 57,8 | 2,27 |
| 16B-2 | 25,4 | 1" | 17,02 | 8,28 | 15,88 | 68,0 | 21,0 | 31,88 | 106,0 | 5,78 |



GRUPO HIBERI