



CADENA FABRICADA SEGÚN NORMA ISO 9001 - ISO 14001 Y API 7F
 CHAIN PRODUCED BY ISO 9001 - ISO 14001 AND API 7F CERTIFIED COMPANY

CADENA ESTIRADA / PRE-STRETCHED CHAINS



SIMPLE

| ISO | p | | b ₁ mm min. | d ₂ mm | d ₁ mm max. | a ₂ mm max. | g mm max. | Carga de rotura | | q kg/m ≈ |
|--------------|--------|------|------------------------------|----------------------|------------------------------|------------------------------|-----------------|-----------------|-------------|----------------|
| | mm | inch | | | | | | minimo KN | medio KN | |
| 06B-1 | 9,525 | 3/8" | 5,72 | 3,28 | 6,35 | 13,5 | 8,26 | 9,0 | 10,7 | 0,40 |
| 08B-1 | 12,7 | 1/2" | 7,75 | 4,45 | 8,51 | 17,0 | 11,81 | 18,0 | 21,1 | 0,68 |
| 10B-1 | 15,875 | 5/8" | 9,65 | 5,08 | 10,16 | 19,6 | 14,73 | 22,4 | 27,4 | 0,91 |
| 12B-1 | 19,05 | 3/4" | 11,68 | 5,72 | 12,07 | 22,7 | 16,13 | 29,0 | 32,3 | 1,12 |
| 16B-1 | 25,4 | 1" | 17,02 | 8,28 | 15,88 | 36,1 | 21,08 | 60,0 | 70,6 | 2,59 |

DOBLE

| ISO | p | | b ₁ mm min. | d ₂ mm | d ₁ mm max. | a ₂ mm max. | g mm max. | e mm | Carga de rotura | | q kg/m ≈ |
|--------------|--------|------|------------------------------|----------------------|------------------------------|------------------------------|-----------------|---------|-----------------|-------------|----------------|
| | mm | inch | | | | | | | minimo KN | medio KN | |
| 06B-2 | 9,525 | 3/8" | 5,72 | 3,28 | 6,35 | 23,8 | 8,26 | 10,24 | 16,9 | 19,2 | 0,76 |
| 08B-2 | 12,7 | 1/2" | 7,75 | 4,45 | 8,51 | 31,0 | 11,81 | 13,92 | 32,0 | 38,0 | 1,31 |
| 10B-2 | 15,875 | 5/8" | 9,65 | 5,08 | 10,16 | 36,2 | 14,73 | 16,59 | 44,5 | 57,3 | 1,79 |
| 12B-2 | 19,05 | 3/4" | 11,68 | 5,72 | 12,07 | 42,2 | 16,13 | 19,46 | 57,8 | 65,7 | 2,22 |
| 16B-2 | 25,4 | 1" | 17,02 | 8,28 | 15,88 | 68,0 | 21,08 | 31,88 | 113,7 | 137,5 | 5,03 |